

Courier flags

- **COURIER_DATA_LOCK_ENABLED** enables the data lock.
- **COURIER_ENHANCED_ENABLED** enables data binding and visualization, which enables Candra graphics engine support.
- **COURIER_ENHANCE-SERIALIZATION_ENABLED** activates message serialization.
- **COURIER_MESSAGING_MONITOR_ENABLED** enables messaging monitor.
- **COURIER_PLATFORM** defines the platform Courier is built for.
- **COURIER_PLATFORM_CONFIG** defines the platform configuration Courier is built for.
- **COURIER_PREBUILT_LIB_DIR** sets the location of pre-built Courier library root folder. Compiler and build configuration are added.
- **COURIER_RENDERING_MONITOR_ENABLED** enables rendering monitor.
- **COURIER_USE_PREBUILT_LIBS** uses pre-built Courier libraries in solution instead of Courier sources.
- **COURIER_CMAKE_LOGGING_LEVEL** defines the verbosity level of Courier CMake system
- **COURIER_MESSAGE_SERIALIZATION_ENABLED** activates message serialization
- **COURIER_CUSTOM_INJECT_WIDGET_BASE_ENABLED** enables the use of customized includes.
- **COURIER_PLATFORMDEFS_DIR** sets customer specific search path for Courier platform definitions.
- **COURIER_SCRIPTING_ENABLED** enables Courier scripting system support.

Revision #2

Created 2023-03-07 07:28:23 UTC by Tsuyoshi.Kato

Updated 2025-04-15 10:18:34 UTC by Tsuyoshi.Kato