

Candera V3.0.1

Release Date: August 14, 2014

To keep backwards compatibility for any interface change in the public API the old interface has been kept and marked as deprecated. The deprecated interfaces will be removed in future versions. Compiler warnings will be generated when using a deprecated interface through the usage of Candera Macro `CANDERA_DEPRECATED_3_1_0`.

- [Candera Engine 2D](#)
- [Candera Engine 3D](#)
- [Candera AssetLoader](#)
- [Candera Device](#)
- [TextEngine](#)

Candera Engine 2D

Checks on set Bounding and Layout Rectangle

New methods [Node2D::IsBoundingRectangleSet](#) and `Node2D::IsLayoutingRectangleSet` have been introduced. BoundingBox calculation of groups and layout of [DefaultLayouter](#) now also consider set bounding boxes on groups.

New feature flag to disable 2D Layout

A new CMake feature flag `CANDERA_2D_LAYOUTING_ENABLED` (default ON) has been introduced, which allows to remove the whole code for dynamic layout.

Candera Engine 3D

Camera: Set up and lookAt vectors in one call

[Camera::SetUpAndLookAtVectors](#) allows setting the up and lookAt vectors at once. It is useful to avoid situations like when setting one of them could cause fail because is collinear with the default value of the other one, which is going to be changed anyway.

Candera AssetLoader

Release Orphaned Cached Objects

A new method [DefaultAssetProvider::ReleaseOrphanedObjects](#) has been introduced to release all cached shared objects that are only referenced by the [DefaultAssetProvider](#). Objects referenced also from other places are maintained so that they may be retrieved at a later time.

Candera Device

Mapping from OpenGL to Candera for Blend Settings

The GLTypeMapper has been enhanced to map blend factor and operation from OpenGL type to [Candera](#) enums. The functions are used to resync the render state cache for blend factor and blend operation.

TextEngine

Configuration for Hinting and Anti-Aliasing

New interfaces allow configuration of hinting. According functionality is supported by FreeType integration.

The new method [TextRendering::Font::SetRequestedGlyphFormat](#) allows also to choose value "Monochrome" as [Candera::TextRendering::GlyphBitmap::Format](#) which disables anti-aliasing but might give good results with small font sizes or in use cases with low color resolution (e.g. monochrome display).

See also:

[TextRendering::Font::SetHintingMode](#)

[TextRendering::Font::SetHintingEnabled](#)

[TextRendering::Font::SetAutohintEnabled](#)

[TextRendering::Font::SetForceAutohintEnabled](#)

[TextRendering::Font::SetRequestedGlyphFormat](#)
